

Dataman 48Pro2AP

The Dataman 48Pro2AP is a super fast industrial universal programmer with ISP capabilities and USB 2.0 connectivity. The 48Pro2AP is built to meet the demands of production programming with automated handlers and ATE machines.

Supporting over 58,000 (April 2015) devices with new support being added monthly, the Dataman 48Pro2AP gives you the freedom to choose the optimal device for your requirements.



Hardware

General

- The 48Pro2AP programmer offers the same advanced features as the 48Pro2 programmer but in a form suitable for industrial applications such as automated handlers and ATE machines.
- The footprint of the Dataman 48Pro2AP has been reduced by 33% compared with the 48Pro2 to minimise the handler's movement and maximises throughput.
- Mechanically stable case designed to be immune to vibration during operation. The case offers multiple fixing points allowing for easy integration with automated handlers and ATE machines.
- FPGA based totally reconfigurable 48 powerful TTL pindrivers provide H/L/pull_up/pull_down and read capability for each pin of the socket. Advanced pindrivers incorporate high-quality high-speed circuitry to deliver signals without overshoot or ground bounce for all supported devices. Pin drivers operate down to 1.8V so you'll be ready to program the full range of tomorrow's advanced low-voltage devices.
- The programmer performs device insertion and contact tests before programming each device. These capabilities, supported by overcurrent protection and signature-byte check, help prevent chip damage due to operator error.
- Selftest capability allows diagnostics in the software to thoroughly check the health of the programmer.
- Built-in protection circuits eliminate damage to the programmer and/or programmed devices due to environment or operator failure. All the inputs of the 48Pro2AP programmer are protected against ESD up to 15kV.
- The 48Pro2AP programmer performs programming verification at the marginal levels of supply voltage, improving programming yield and guaranteeing long data retention.
- Socket converters utilise an extremely stable design and are constructed to meet the additional demands of automated handlers. This design allows them to retain exact positioning even after changing.
- Wide range of socket converters are available to handle devices in PLCC, SOIC, PSOP, SSOP, TSOP, TSSOP, TQFP, QFN (MLF), SDIP, BGA and other packages.

Programmer Specification

- 1 x universal programming module
- Power and operation status LEDs
- USB 2.0 high-speed compatible port
- Protection against surge and ESD on power supply input
- Grounding point

Features...

- Optimised for use in automated handlers and ATE machines
- Over 58,000 (April 2015) devices supported with new devices added monthly
- Mechanically stable case design with multiple fixing points
- ISP capable using the JTAG interface
- Hi-speed USB 2.0 connectivity
- Easy to use software compatible with the latest operating systems including Windows 8
- Comprehensive 3 years parts and labour warranty
- Free life-time software updates

Module Specification

Base Unit (DAC)

- On-board intelligence: powerful microprocessor and FPGA based state machine
- Three D/A converters for VCCP, VPP1, and VPP2, controllable rise and fall time
- VCCP range 0..8V/1A
- VPP1, VPP2 range 0..26V/1A
- Selftest capability

Socket Connector

- Pindrivers: 48 universal
- VCCP/VPP1/VPP2 can be connected to each pin
- Perfect ground for each pin
- FPGA based TTL driver provides H, L, CLK, pull-up, pull-down on all pindriver pins
- Analog pindriver output level selectable from 1.8V up to 26V
- Current limitation, overcurrent shutdown, power failure shutdown
- ESD protection on each pin (IEC1000-4-2: 15kV air, 8kV contact)
- Continuity test: each pin is tested before every programming operation

ISP Connector

- 20-pin male type with missinsertion lock
- 6 TTL pindrivers, provides H, L, CLK, pull-up, pull-down; level H selectable from 1.8V up to 5V to handle all (including low-voltage) devices
- 1x VCCP voltage (range 2V..7V/100mA), can be applied to two pins
- Programmed chip voltage (VCCP) with both source/sink capability and voltage sense
- 1x VPP voltage (range 2V..25V/50mA), can be applied to six pins
- Target system supply voltage (range 2V..6V/250mA)
- ESD protection on each pin (IEC1000-4-2: 15kV air, 8kV contact)
- Two output signals, which indicate state of work result = LED OK and LED Error (active level: min 1.8V)
- Input signal, switch YES! equivalent (active level: max. 0.8V)

Software

User Interface

Production Mode Control

- This part of the software is focused on the easy monitoring of high-volume production operations.
- Operator-friendly control software combines many powerful functions with ease of use. Graphical user interface provides an overview of important information, reducing the burden on the operator with unnecessary details.
- Project files are used to control the 48Pro2AP and contain user data, chip programming setup, chip configuration, auto programming command sequence. This helps minimize operator error as the project file is normally created by an engineer and then passed to the operator. The optional protected mode can be set avoiding unwanted changes to the project file.
- Each chip may be programmed with different data such as serial number, configuration and calibration information.

Engineering Mode Control

- This part of the software is focused on the quick and easy preparation of the project file for usage in the production mode control software.
- Each programming module is driven by an easy-to-use control program with pull-down menus, hot keys and on-line help. Selecting a device is performed by its class, by manufacturer or simply by typing a fragment of the vendor name and/or part number.
- Standard device-related commands (read, blank check, program, verify, erase) are enhanced by test functions (insertion test, signature-byte check) and additional special functions (auto-increment serialisation, production mode - programming starts immediately after chip is inserted).
- All known data formats are supported. Automatic file format detection and conversion performed during loading of file.
- The software provides extensive information about programmable devices including detailed drawings of all available packages. The software also provides explanations of chip labelling (prefixes and suffixes).

The Dataman 48Pro2AP supports over 58,000 (April 2015) of the most popular devices in use today - with future devices being added monthly.

Programmer (Socket Connector)

EPROM, EEPROM, Flash EPROM, NAND FLASH, eMMC, LBA-NAND, mDOC H3, Multi-chip, FRAM, MRAM, NV RAM, PROM, Serial E(E)PROM, Serial Flash, Configuration (EE)PROM, 1-Wire E(E)PROM, PLD, FPGA, Clocks, Microcontrollers

Programmer (ISP Connector)

Serial E(E)PROM, 1-Wire E(E)PROM, Serial Flash, Microcontrollers, PLD, FPGA

Package Includes

- **Dataman 48Pro2AP Super Fast Universal 48-Pin Programmer**
Dimensions: 88 x 205 x 61mm (3.5 x 8.1 x 2.4inches)
Weight: 1.15Kg (2.54lbs)
- Switching Power Adapter
Operating voltage: 100-240V AC
Power consumption: max. 20W active
- Moulded USB cable
- ISP cable
- Diagnostic POD for selftest of the programmer
- Diagnostic POD for selftest of the ISP connector
- Fixing screw for programming module (x2)
- User manual
- Software
- Optional range of adapters and socket converters also available

Warranty and Support

- 30 day money back guarantee* - If you don't like it, send it back.
- Three year guarantee - Three years parts and labour warranty, on the 48Pro2AP universal programmer.
- Life-Time Technical Support - 48Pro2AP technical support is available free via our website and telephone helpdesk for life.
- Life-Time Software Updates - 48Pro2AP software updates are available free via our website for life.

*Applies to orders from UK/US offices only



www.dataman.com

IN THE UK...

Dataman Programmers Ltd.
Unit 2 Newton Hall, Dorchester
Road, Maiden Newton, Dorset
DT2 0BD, UK
Tel (01300) 320719
Fax (01300) 321012

IN THE US...

Dataman Inc.
215 East Michigan Avenue
Orange City, Florida 32763 USA
Tel (386) 774-7785
Fax (386) 774-7796

Available from...