



The Dataman MEMPro is a PC based universal 40-pin memory programmer with USB 2.0 connectivity. The MEMPro is built to meet the demands of development labs and field engineers for specialized programming.

Dataman MEMPro is a small, fast and powerful programmer supporting a huge range of programmable memory types – EPROM, EEPROM, NVRAM, Flash EPROM and serial EEPROM – including low voltage types. MEMPro isn't only a programmer, but also a static RAMs tester.

Hardware

General

- 40 powerful TTL pindrivers provide H/L/pull_up/pull_down and read capability for each pin of the socket. Advanced pindrivers incorporate high-quality high-speed circuitry to deliver signals without overshoot or ground bounce for all supported devices. Pin drivers operate down to 1.8V so you'll be ready to program the full range of today's advanced low-voltage devices
- The programmer performs device insertion tests and contact checks before it programs each device. These capabilities, supported by signature-byte check help prevent chip damage due to operator error
- MEMPro programmer performs programming verifications at the marginal level of supply voltage, which improves programming yield, and guarantees long data retention
- Easily upgradeable to the 40Pro programmer
- Various socket converters are available to handle device in PLCC, SOIC, SSOP, TSOP, TSSOP, TQFP, QFN (MLF) and other packages

Base unit (DAC)

- Two D/A converters for VCCP and VPP, controllable rise and fall time
- VCCP range 2V..7V/350mA
- VPP range 2V..25V/200mA
- USB 2.0/1.1 compatible interface
- Auto calibration
- Self test capability

- Over 16,000 (April 2015) devices supported with new devices added monthly
- Intelligent pin drivers operate down to 1.8V so you'll be ready to program the full range of tomorrow's advanced low-voltage devices
- Hi-speed USB 2.0 connectivity
- Easy to use software compatible with the latest operating systems including Windows 8
- Upgradeable to 40Pro programmer
- Comprehensive 1 year parts and labour warranty
- Free life-time software updates

ZIF socket pindriver

- 40-pin DIL ZIF (Zero Insertion Force) socket accepts both 300/600 mil devices up to 40-pins
- Pindrivers: 40 TTL pindrivers, specialized GND/VCC/VPP pindriver
- FPGA based TTL driver provides H, L, CLK, pull-up, pull-down on all pindriver pins; level H selectable from 1.8V up to 5V
- Continuity test: each pin is tested before every programming operation

ISP connector (useable after upgrade to 40Pro)

- 10-pin male type with miss insertion lock
- 6 TTL pindrivers, provides H, L, CLK, pull-up, pull-down; level H selectable from 1.8V up to 5V to handle all (low-voltage including) devices
- 1x VCCP voltage (range 2V..7V/100mA) and 1x VPP voltage (range 2V..25V/50mA)
- Programmed chip voltage (VCCP) with both source/sink capability and voltage sense

Software

User Interface

- Programmer is driven by an easy-to-use control program with pull-down menus, hot keys and on-line help. Selection of device is performed by its class, by manufacturer or simply by typing a fragment of vendor name and/or part number
- Standard device-related commands (read, blank check, program, verify, erase) are enhanced by some test functions (insertion test, signature-byte check), and some special functions (autoincrement)
- All known data formats are supported. Automatic file format detection and conversion during loading of file
- The rich-featured autoincrement function enables one to assign individual serial numbers to each programmed device - or simply increments a serial number, or the function enables one to read serial numbers or any programmed device identification signatures from a file
- The software also provides extensive information about programmable devices including detailed drawings of all available packages. The software also provides explanations of chip labelling (prefixes and suffixes) for each of the supported chips
- Keeping your programmer software up to date can be a costly business with some programmers. Dataman offers completely FREE software updates whenever you need them. The latest software is always available from our website

The Dataman MEMPro supports over 16,000 (April 2015) of the most popular memory devices in use today - with future devices being added monthly.

Programmer (ZIF socket)

- EPROM: NMOS/CMOS, 27xxx and 27Cxxx series, with 8/16 bit data width, full support of LV series
- EEPROM: NMOS/CMOS, 28xxx, 28Cxxx, 27EExxx series, with 8/16 bit data width, full support of LV series
- Flash EPROM: 28Fxxx, 29Cxxx, 29Fxxx, 29BVxxx, 29LVxxx, 29Wxxx, 49Fxxx series, with 8/16 bit data width, full support of LV series
- Serial E(EP)ROM: 24Cxxx, 24Fxxx, 25Cxxx, 45Dxxx, 59Cxxx, 25Fxxx, 25Pxxx, NVM3060, 85xxx, 93Cxxx, full support for LV series
- Configuration (EE)PROM: 37LVxx, XC17xxxx, AT17xxx, LV series including
- NV RAM: Dallas DSxxx, SGS/Inmos MKxxx, SIMTEK STKxxx, XICOR 2xxx, ZMD U63x series

Package Includes

- **Dataman MEMPro Universal Memory Programmer**
Dimensions: 160x95x35 mm (6.3x3.7x1.4 inches)
Weight: 500g (17.65 oz)
- Switching Power Supply Adapter
Input: 100-240V @ 50-60Hz Et 400mA
Output: 15V @ 0.5A, 7.5W
- Moulded USB Cable
- ISP cable (useable after upgrade to 40Pro)
- Diagnostic POD for self test of the programmer
- Anti-dust cover for ZIF socket
- User manual
- Software
- Optional range of adapters and socket converters also available

Warranty and Support

- 30 day money back guarantee* - If you don't like it, send it back
- One year guarantee - One year parts and labour warranty, on the MEMPro device programmer
- Life-Time Technical Support - MEMPro technical support is available free via our website and telephone helpdesk for life
- Life-Time Software Updates - MEMPro software updates are available free via our website for life

*Applies to orders from UK/US office only



www.dataman.com

IN THE UK...

Dataman Programmers Ltd.
Unit 2 Newton Hall, Dorchester
Road, Maiden Newton, Dorset
DT2 0BD, UK
Tel (01300) 320719
Fax (01300) 321012

IN THE US...

Dataman Inc.
215 East Michigan Avenue
Orange City, Florida 32763 USA
Tel (386) 774-7785
Fax (386) 774-7796

Available from...